



Intelligent Waveguide Inflator Dehydrator Microwave Antenna Accessories

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Famous
- Certification: CE ISO9001
- Model Number: Intelligent waveguide inflator Dehydrator
- Minimum Order Quantity: 1 SET
- Price: Negotiable
- Packaging Details: Standard export packaging/customizable packaging
- Payment Terms: T/T L/C



Product Specification

- Name: Intelligent Waveguide Inflator Dehydrator
- Work Pressure: 2.5-25KPa
- Nix Charge Flux: 15ascend/minute
- Work Voltage: AC 220V±10%50-60Hz DC48V±159%
- Power Consume: (Charge State)30VA (maintain Voltage State)5VA
- Air Feed Out Put: 4
- Mainframe Gas Tightness: Maintain Voltage 24hours Later Pressure Reduce Less Than 3KPa
- Noise: ≤45dB
- MTBF: 30000hou
- Size: 370×260×120mm
- Weight: 8kg
- Highlight: **2.5-25KPa microwave antenna accessories, microwave components, microwave antenna intelligent waveguide inflator dehydrator**

for more products please visit us on mw-antenna.com

Product Description

Intelligent waveguide inflator Dehydrator

Dehydrator is mainly used to charge for waveguide in the field of microwave station. This equipment can maintain dry air pressure in the communication line automatically in order to keep out of moist air and water and ensure the quality transmit signal.

Our machine has advantage of small size, reasonable in inner structure, good manufacture, install easily and operate safely.

Technic Index

| | |
|-------------------------|---|
| work pressure | 2.5-25KPa |
| Nix charge flux | 15ascend/minute |
| voltage | AC 220V±10%50-60Hz DC48V±159% |
| Power consume | (Charge state)30VA保(maintain voltage state)5VA |
| Air feed out put | 4 |
| Mainframe gas tightness | Maintain voltage 24hours later pressure reduce less than 3KPa |
| | -55~+70 |
| noise | ≤45dB |
| MTBF | 30000hou |
| size | 370×260×120mm |
| Weight | 8kg |

